

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS

Test Document No.: VPS-255E
Requested by: Viking Packing Specialist
Performed by: Viking Packing Specialist
Date: 6-27-22

1. Product Tested:

Packaging Nomenclature: Combination Packaging
Outer Package: 4H2 (HSC single wall corrugated plastic box)
Dimensions: 14.5" x 14" x 18.625" (outer dims/ inches)
Inner Package: See appendix B for approved inners
Maximum gross wt. (kg): 22
Viking Part No.: VPS-255E
Customer Part No.: N/A

2. Object of Test:

Determine performance of package design according to PASS/FAIL criteria set forth by the United States Code of Federal Regulations Title 49 sections 178.603, 178.606, and 178.608, to Packing Group I standards.

3. Tests Performed:

TEST	SPEC	INTENSITY	RESULTS
Drop	49 CFR 178.603	22 kg	PASS
Stacking	49 CFR 178.606	135 kg	PASS
Vibration	49 CFR 178.608	1 HOUR	PASS

Viking Packing Specialist certifies that samples of the package described in this report were tested as described above and met all testing requirements. This package is also certified under IMDG, ICAO, IATA, and the UN Recommendations on the Transport of Dangerous Goods. It is the responsibility of the end user to determine authorization of use under these regulations. The use of other packaging methods or components other than those documented in this report may render this certification invalid.



Certified By: _____
Special Projects & DG Manager
Eric Curtis



Approved By: _____
President
David Weilert

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS

TEST METHODS & RESULTS

1. DROP TEST- 49 CFR 178.603

Packages were conditioned to -20°C (-4°F) prior to testing. Five (5) filled packages, closed as for shipment, were subjected to a free fall drop from a height of 1.8 m (5.9 ft) onto a solid concrete floor as follows:

Containers	Point of Impact	Result
#1	Flat onto the bottom panel	PASS
#2	Flat onto the top panel	PASS
#3	Flat onto the long side panel	PASS
#4	Flat onto the short side panel	PASS
#5	Onto the bottom manufacturer's joint corner	PASS

2. STACKING TEST- 49 CFR 178.606

Three (3) filled containers were closed as for shipment and subjected to a static compression load of 135 kg, equivalent to a 3-meter-high stack of identical packages, continuously for 24 hours.

Containers	Actual Load	Result
#1	135 kg	PASS
#2	135 kg	PASS
#3	135 kg	PASS

3. VIBRATION STANDARD- 49 CFR 178.608

Three (3) filled samples, closed as for shipment, were placed on a vibration platform having 25.4 mm peak-to-peak displacement and vibrated in normal shipping orientation for one (1) hour such that a 1.6 mm thick piece of material could be passed between the bottom of the samples and the platform. Immediately thereafter, the packages were removed from the platform and examined for leakage.

Containers	Vibration	Result
#1	1 HOUR	PASS
#2	1 HOUR	PASS
#3	1 HOUR	PASS


Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

<p style="text-align: center;">UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS</p>
--

4. Packaging's tested, certified, and provided by Viking Packing Specialist bear the marking:



4H2/X22/S/**

USA/M4563

**Denotes two-digit year of manufacture

See appendices for additional information regarding this report. Information is included as follows.

- Appendix A – Specific outer package information.
- Appendix B – Inner and supplementary packaging/configurations tested in this outer package
- Appendix C – Packing/Closure Instructions.

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS

Appendix A – Outer Package Detail

Designated Packaging Code:	4H2
Dimensions:	13.375" x 12.625" x 17.25" (Inner Cavity)
Style:	HSC Single wall corrugated plastic
Marked max. gross wt. (kg):	22
Max. net weight (kg)	17
Closure:	3" hot-melt tape. Mfg.: Shurtape. Mfg. P/N: HP-200.

*Flaps of outer box are sealed with solid SPVC vinyl tape Mfg.: Preferred Tape. Mfg.
P/N: CVT-636

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

<p>UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS</p>

Appendix B – Inner Package Detail

NOTES

1. Inner packages of equal or smaller size than those listed may be used in this combination package without further testing if:
 - They are of similar design to those originally tested,
 - The material of construction is equivalent to or stronger than the material originally tested,
 - The closures are of similar design and are no larger than those used for testing
 - Additional cushioning material is used, and the inner packages are secure.
 - Inner packages are oriented in the same way as tested, and
 - The gross package weight does not exceed that of the tested package.
2. Fewer inner packages than listed may be used in this combination package without further testing if:
 - Additional cushioning is used to fill void space, and
 - Movement of inner packages is prevented

See the following for inner packages and supplementary packages tested in this outer package.

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS

Appendix B – Inner Package Detail (continued)

The outer package was tested with configurations of inner package as follows. Please refer to Table 1 (attached) for particular parts allowed in this package. Refer to packing/closure instructions for supplemental packaging requirements. Steel weights were used to achieve test weight.

STYLE	MAX QTY.	Dims (inches)	NET WT. (EA)
Oxygen Gen. (in mfg. pkg.)	12	13.5x3.5x3.5	1 kg
Oxygen Gen. (unpacked)	8	11" L x 4" D	2 kg
Oxygen Gen. (unpacked)	8	10" L x 3" D	2 kg
12 Oxygen Gen. in mfg. pkg.	1	13.5x12.5x17.5	17 kg

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

Intermediate Packaging:

Inner packages are placed within an intermediate container constructed out of 1/8" acrylic coated panel board. Container is assembled together using 3" Paper Masking Tape (Mfg.: Shurtape. Mfg. P/N: 104118). Inner seams are sealed using white silicone. Container lid is constructed out of double laminated 1/8" acrylic coated panel board creating a friction fit lid which is secured to container by means of the outer telescoping plastic corrugated container. Container is coated with a latex fire-retardant paint, (Mfg.: Benjamin Moore Mfg. P/N: 220 White P59 01). Cavity dimensions are 13.5" x 12.625" x 17.25".

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

<p style="text-align: center;">UNITED NATIONS PERFORMANCE ORIENTED PACKAGING TEST RESULTS</p>
--

Packing/Closure Instructions – VPS-250E,250EB,253E,255E

1. Inspect container, and all components for damage. If container is found to be free from damage proceed to step 2. If container is damaged; procure a different container and inspect.
2. Slide top plastic HSC container off bottom half.
3. Remove intermediate package's lid.
4. Place inner package(s) into container. Refer to Table 1 for number of inner packages allowed in each shipping container. When only one inner package is shipped within the outer container, fill all void space with bubble wrap. When shipment is made with more than one inner package. When shipment consists of:
 - a. Panels or PBEs: Place inner packages into container and fill all void space with bubble wrap.
 - b. Generators contained in manufacturer's individual packaging: Evenly space inner packages into container leaving as much space between inner packages as possible. Fill all void space with bubble wrap.






SIZE: 1/2"
Bubble: 1 1/4" diameter
MATERIAL: Polyethylene and Nylon. Not biodegradable.
 - c. Generators with no supplementary means of containment: Wrap each generator with 1: 24" x 10" piece of Super wool (mfg.) insulation material. Evenly space inner packages into container leaving as much space between inner packages as possible. Fill all void space with bubble wrap.
5. Close intermediate package's lid.
6. Replace top plastic HSC container over bottom half and secure using 3" hot-melt tape, (Mfg.: Shurtape. Mfg. P/N: HP-200), one strip of tape overlapping entire box aligning with flap seams (top and bottom ends).

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518


Testing Photos

Bottom Drop	Top Drop
	
End Drop	Wall Drop
	
Mfg. Corner	
	

Viking Packing Specialist

1578A North 105th East Avenue • Tulsa, OK 74116

Phone: (800) 788-8525 • Fax: (918) 252-5518

Stack Weight	Vibration
	

120"/18.63" = 7-1=6 x 22kg=132kg=300lbs

Height	
	